


KERN ABS 320-4N

KERN

The bestseller in analytical balances, with high-quality single-cell weighing system



Display	
Display digit height	14 mm
Display backlight	no
Display screen size	115×32 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	213×333×338 mm
Dimensions rectangular draught shield - inner (W×D×H)	174×162×227 mm
Dimensions rectangular draught shield - outer (W×D×H)	201×220×256 mm
Dimensions weighing surface (Ø)	91 mm
Material housing	plastic
Material display housing	Plastics
Material weighing plate	stainless steel
Material draught shield	glass
Levelling feet adjustable	✓

Functions	
Number of keys for operation	6
Tare function	manual (multi)
Percentage determination	✓
Counting function	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Standby function	✓
Recipe/summing level	Rez A (Net total)
Sum memory function	✓
Underfloor weighing	None
Interfaces	RS-232 (optional)

Counting	
Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Counting reference weight can be entered	✓
Reference quantity	5, 10, 20, 50, 100
Counting resolution (laboratory conditions)	320.000

Power Supply	
Input voltage power supply / power [Max]	110 V - 230 V AC
Input voltage device / power [Max]	12 V DC, 1000 mA

Category	
Brand	KERN
Product category	Laboratory balances
Product group	Analytical balances

Measuring System	
Readability [d]	0,0001 g
Readability carat [d] (ct)	0,001 ct
Weighing capacity [Max]	320 g
Weighing capacity [Max] (ct)	1600 ct
Eccentric loading at 1/3 [Max]	0,0005 g
USP Minimum weight of sample (k = 2, U = 0.1%)	400 mg
Reproducibility	0,0002 g
Linearity	± 0,0003 g
Weighing system	Single-Cell
Resolution	3.200.000
Units	g mg tl (Tw) ozt tl (Singap, Malays) ct oz tl (Cn)
Default unit	g
Stabilization time	3 s
Warm-up time	8 h
Adjustment options	Adjusting with external weight
Recommended adjusting weight	300 g (E2)
Possible calibration points	150 g

Approval	
CE mark	✓

KERN ABS 320-4N



The bestseller in analytical balances, with high-quality single-cell weighing system

Plug-in power supply type	Power adapter
Supplied plug-in power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH

Environmental conditions

Humidity of environment [Min]	20 %
Humidity of environment [Max]	85 %
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C

Packing & Shipping

Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	388×570×530 mm
Net weight approx.	6 kg
Gross weight approx.	9 kg

Services (optional)

Article number for DAkkS calibration	963-101
Article number for certificate of conformity (verification)	969-517

Piktogramme

STANDARD



OPTION

