


KERN BID 3T-3DLM

Dual-range floor scale with EC type approval [M] and the best price-to-performance ratio



Pattern approval for conformity assessment	✓
Accuracy classe	III
Verification scale interval [e]	0,5 kg; 1 kg

Display	
Display type	LCD
Display digit height	25 mm
Display backlight	✓
Display screen size	110×35 mm
Languages of the user interface	Symbol language

Construction	
Dimension display device (W×D×H)	268×115×80 mm
Dimensions weighing platform (W×D×H)	1500×1500×108 mm
Dimensions weighing surface (W×D)	1500×1500 mm
Material display housing	Plastics
Material weighing plate	steel, powder-coated
Material platform	steel, powder-coated
Material load cell(s)	steel
Wall mount	✓
Cable length	5 m
Display device cable length	5 m
Allowed cable length display device [Max]	15 m
Levelling feet adjustable	✓
Load cells - number	4

Functions	
Number of keys for operation	7
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min off 5 min 30 min 15 min
PreTare function	✓
Tare function	manual (multi)
Percentage determination	✓
Counting function	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Function for averaging under unstable weighing conditions	✓
Recipe/summing level	Sum A
Alibi memory	optional internal memory
Alibi memory - number of memory spaces	250.000
Interfaces	RS-232 standard Ethernet (optional)

Category	
Brand	KERN
Product category	Industrial scales
Product group	Floor scales

Measuring System	
Readability [d]	500 g; 1000 g
Weighing capacity [Max]	1500 kg; 3000 kg
Number of weighing ranges	2
Eccentric loading at 1/3 [Max]	2,5 kg; 5 kg
Minimum weight [Min]	10 kg; 20 kg
Reproducibility	0,5 kg; 1 kg
Linearity	± 1,5 kg; 3 kg
Linearisation in dots	3
Weighing system	Strain gauge
Resolution	3.000, 3.000
Tare range	3000 kg
Units	kg g lb oz PCS tJ HJ
Units (if device is conformity assessed)	kg
Default unit	kg
Stabilization time	2 s
Warm-up time	10 min; 10 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	3000 kg (M1)
Loadcell type	KELI SQB
Load cell connection	4-guide

Approval	
CE mark	✓
Conformity assessment possible ex works	✓

KERN BID 3T-3DLM



Dual-range floor scale with EC type approval [M] and the best price-to-performance ratio

	factory) USB (optional, factory) WiFi (optional, factory) Alibi memory (optional, factory) USB-Host/Master (optional, factory) Verification plug (optional, factory) Bluetooth BLE (v4.0) (optional, factory)
IP protection - display	IP65
IP protection - load cell	IP67

Power Supply

Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0.4 A max
Input voltage device / power [Max]	12 V DC, 1000 mA
Plug-in power supply type	Power adapter
Supplied plug-in power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery	6 V; 1.3 Ah
Rechargeable battery charging time	3 h
Rechargeable battery operating time - backlight on	26 h
Rechargeable battery operating time - backlight off	43 h
Battery	no battery

Environmental conditions

Humidity of environment [Min]	0 %
Humidity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C

Packing & Shipping

Readability force [d] (N)	2 d
Shipping method	Freight
Dimensions packaging (WxDxH)	1550x1550x265 mm
Net weight approx.	155 kg
Gross weight approx.	180 kg

Services (optional)

Article number for adjustment at the location of installation	961-252
---	---------

Article number for conformity assessment 965-232

Article number for DAkkS calibration 963-132

Article number for certificate of conformity (verification) 969-517

Piktogramme

STANDARD



OPTION



FACTORY

