KERN FCB 6K0.5



Bench scale with second display on the backside of the scale



Category	
Brand	KERN
Product category	Industrial scales
Product group	Bench scales

Measuring System	
Readability [d]	0,5 g
Weighing capacity [Max]	6000 g
Eccentric loading at 1/3 [Max]	2,5 g
Reproducibility	0,5 g
Linearity	± 1,5 g
Weighing system	Strain gauge
Resolution	12.000
Units	kg g dwt tl (Tw) tl (HK) ozt mo lb oz ffa tol
Default unit	g
Stabilization time	3 s
Warm-up time	30 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	6 kg (F2)
Possible calibration points	2 kg; 4 kg; 6 kg

Adjustment options	weight
Recommended adjusting weight	6 kg (F2)
Possible calibration points	2 kg; 4 kg; 6 kg
Approval	
CE mark	✓
Display	
Display digit height	25 mm
Construction	
Dimension housing (W×D×H)	270×323×110 mm

Dimensions weighing platform (W×D×H)	252×228×12,5 mm
Dimensions weighing surface (W×D)	253×228 mm
Material housing	plastic
Material weighing plate	stainless steel

Functions	
Number of keys for operation	5
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min off
Tare function	manual (multi)
Percentage determination	✓
Counting function	✓
Function for averaging under unstable weighing conditions	/
Recipe/summing level	Rez A (Net total)
Underfloor weighing	None
Interfaces	RS-232 standard

Smallest piece weight when piece counting - laboratory conditions Smallest piece weight when piece counting - normal conditions Reference quantity Counting resolution (laboratory conditions) 1 g 10 g 5, 10, 20, 25, 50 6.000	Counting	
counting - normal conditions Reference quantity Counting resolution (laboratory 6 000		1 g
Counting resolution (laboratory		10 g
, , , , , , , , , , , , , , , , , , , ,	Reference quantity	5, 10, 20, 25, 50
,	Counting resolution (laboratory conditions)	6.000

Power Supplay	
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	9 V, 300 mA
Plug-in power supply type	Power adapter
Supplied plug-in power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery	FCB-A01
Rechargeable battery charging time	10 h
Rechargeable battery operating time - backlight on	5 h
Rechargeable battery operating time - backlight off	10 h
Battery	9 V block

KERN FCB 6K0.5



Bench scale with second display on the backside of the scale

Battery operating time	12 h

Environmental conditions Humity of environment [Max] 80 % Ambient temperature [Min] 5 °C Ambient temperature [Max] 35 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	334×495×185 mm
Net weight approx.	3,0 kg
Gross weight approx.	3,4 kg

Services (optional)	
Article number for adjustment at the location of installation	961-248
Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Piktogramme

STANDARD



OPTION

