

KERN FCB 8K0.1

KERN

Bench scale with second display on the backside of the scale



Construction

Dimension housing (W×D×H)	270×323×110 mm
Dimensions weighing platform (W×D×H)	252×228×12,5 mm
Dimensions weighing surface (W×D)	253×228 mm
Material housing	plastic
Material weighing plate	stainless steel

Functions

Number of keys for operation	5
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min off
Tare function	manual (multi)
Percentage determination	✓
Counting function	✓
Function for averaging under unstable weighing conditions	✓
Recipe/summing level	Rez A (Net total)
Underfloor weighing	None
Interfaces	RS-232 standard

Counting

Smallest piece weight when piece counting - laboratory conditions	200 mg
Smallest piece weight when piece counting - normal conditions	2 g
Reference quantity	5, 10, 20, 25, 50
Counting resolution (laboratory conditions)	40.000

Power Supply

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	9 V, 300 mA
Plug-in power supply type	Power adapter
Supplied plug-in power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery	FCB-A01
Rechargeable battery charging time	10 h
Rechargeable battery operating time - backlight on	5 h

Category

Brand	KERN
Product category	Industrial scales
Product group	Bench scales

Measuring System

Readability [d]	0,1 g
Weighing capacity [Max]	8000 g
Eccentric loading at 1/3 [Max]	0,5 g
Reproducibility	0,1 g
Linearity	± 0,3 g
Weighing system	Strain gauge
Resolution	80.000
Tare range	8000 g
Units	kg g dwt tl (Tw) tl (HK) ozt mo lb oz ffa tol
Default unit	g
Stabilization time	3 s
Warm-up time	120 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	5 kg (F2); 2 kg (F2); 1 kg (F2)
Possible calibration points	2 kg; 4 kg; 6 kg; 8 kg

Approval

CE mark	✓
---------	---

Display

Display digit height	25 mm
----------------------	-------

KERN FCB 8K0.1



Bench scale with second display on the backside of the scale

Rechargeable battery operating time - backlight off	10 h
Battery	9 V block
Battery operating time	12 h

Environmental conditions

Humidity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C

Packing & Shipping

Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	335×400×190 mm
Net weight approx.	2,6 kg
Gross weight approx.	3,4 kg

Services (optional)

Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Piktogramme

STANDARD



OPTION

