KERN FOB 10K-3LM



Compact stainless steel bench scale with EC type approval [M] and special checkweighing display for even more efficient working



Brand	KERN
Product category	Industrial scales
Product group	Food (kitchen/stainless steel/IP6568 protection)
Measuring System	
Readability [d]	5 g
Weighing capacity [Max]	15 kg
Number of weighing ranges	1
Eccentric loading at 1/3 [Max]	0,015 kg
Minimum weight [Min]	0,1 kg
Reproducibility	0,005 kg
Linearity	± 0,01 kg
Weighing system	Strain gauge
Resolution	3.000
Units	kg
Units (if device is conformity assessed)	kg
Default unit	kg
Stabilization time	2 s
Warm-up time	10 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	10 kg (M1)
Possible calibration points	10 kg

Approval

CE mark Conformity assessment possible ex works

Pattern approval for conformity assessment	✓
Accuracy classe	III
Verification scale interval [e]	0,005 kg
D ¹	
Display	
Display digit height	25 mm
Display backlight	1
Construction	
Dimension housing (W×D×H)	256×285×100 mm
Dimensions weighing surface (W×D)	248×198 mm
Material housing	stainless steel
Material weighing plate	stainless steel
Functions	
Auto-off interval(s) in battery	0
mode/rechargeable battery mode	2 min
Tare function	manual (multi)
Tolerance weighing	1
Tolerance weighing - type of signal	visual
IP protection - complete device	IP67
Power Supplay	
Power Supplay Input voltage power supply / power [Max]	230 V AC, 50 Hz
Input voltage power supply /	230 V AC, 50 Hz 12 V, 500 mA
Input voltage power supply / power [Max]	
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply	12 V, 500 mA
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for	12 V, 500 mA Power adapter Power supply unit
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the	12 V, 500 mA Power adapter
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	12 V, 500 mA Power adapter Power supply unit
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery	12 V, 500 mA Power adapter Power supply unit EURO
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4×1.5 V AA
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4×1.5 V AA 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight off	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight off	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h 66 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min]	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h 66 h

1

1

KERN FOB 10K-3LM



Compact stainless steel bench scale with EC type approval [M] and special checkweighing display for even more efficient working

Packing & Shipping	
Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	420×305×180 mm
Net weight approx.	3,8 kg
Gross weight approx.	4,8 kg
Services (optional)	
Article number for adjustment at the location of installation	961-248
Article number for conformity assessment	965-228
Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Piktogramme

STANDARD



OPTION

DAkks +3 days

FACTORY

