KERN FOB 1K-4LM



Compact stainless steel bench scale with EC type approval [M] and special checkweighing display for even more efficient working



Brand	KERN
Product category	Industrial scales
Product group	Food (kitchen/stainless steel/IP6568 protection)
Measuring System	
Readability [d]	0,5 g
Weighing capacity [Max]	1500 g
Number of weighing ranges	1
Eccentric loading at 1/3 [Max]	2,5 g
Minimum weight [Min]	10 g
Reproducibility	0,5 g
Linearity	± 1,5 g
Weighing system	Strain gauge
Resolution	3.000
Units	g
Units (if device is conformity assessed)	g
Default unit	g
Stabilization time	2 s
Warm-up time	10 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	1 kg (M1)
Possible calibration points	1,5 kg

Approva

CE mark Conformity assessment possible ex works

Pattern approval for conformity assessment	✓
Accuracy classe	111
Verification scale interval [e]	0,5 g
Dioplay	
Display	
Display digit height	25 mm
Display backlight	<i>√</i>
Construction	
Dimension housing (W×D×H)	256×285×100 mm
Dimensions weighing surface (W×D)	248×198 mm
Material housing	stainless steel
Material weighing plate	stainless steel
Functions	
Auto-off interval(s) in battery	
mode/rechargeable battery mode	2 min
Tare function	manual (multi)
Tolerance weighing	1
Tolerance weighing - type of signal	visual
IP protection - complete device	IP65
Power Supplay	
Power Supplay Input voltage power supply / power [Max]	230 V AC, 50 Hz
Input voltage power supply /	230 V AC, 50 Hz 12 V, 500 mA
Input voltage power supply / power [Max]	
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply	12 V, 500 mA
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	12 V, 500 mA Power adapter
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the	12 V, 500 mA Power adapter Power supply unit
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	12 V, 500 mA Power adapter Power supply unit EURO
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4×1.5 V AA
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4×1.5 V AA 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight off	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight off	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h 66 h
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied plug-in power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Battery Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min]	12 V, 500 mA Power adapter Power supply unit EURO EURO UK CH 4× 1.5 V AA 48 h 48 h 66 h

1

1

KERN FOB 1K-4LM



Compact stainless steel bench scale with EC type approval [M] and special checkweighing display for even more efficient working

Packing & Shipping	
Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	420×305×180 mm
Net weight approx.	3,8 kg
Gross weight approx.	4,8 kg
Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for conformity assessment	965-227
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Piktogramme

STANDARD



OPTION

DAkkS +3 days

FACTORY

