KERN FOB 30K-3NL



Stainless steel bench scale with large weighing ranges and IP67 protection against dust and water spray



Category	
Brand	KERN
Product category	Industrial scales
Product group	Food (kitchen/stainless steel/IP6568 protection)

Measuring System	
Readability [d]	2 g; 5 g
Weighing capacity [Max]	16000 g; 30000 g
Number of weighing ranges	2
Eccentric loading at 1/3 [Max]	10 g; 25 g
Reproducibility	2 g; 5 g
Linearity	± 6 g; 15 g
Weighing system	Strain gauge
Resolution	8.000, 6.000
Units	g lb oz
Default unit	kg
Stabilization time	2 s
Warm-up time	30 min; 30 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	20 kg (M1)
Possible calibration points	20 kg
Approval	

CE mark

Display

Display digit height

Display backlight

	(W×D)
	Material housing
	Material weighing plate
ı	Functions
Ī	Number of keys for operation
	Auto-off interval(s) in battery mode/rechargeable battery mode
•	Tare function
	Underfloor weighing
	IP protection - complete device
	Power Supplay
	Input voltage power supply / power [Max]
	Input voltage device / power [Max
	Plug-in power supply type
	Supplied plug-in power supply
	Plug-in power supply / adapter for countries - optional
	Battery
	Battery operating time
	Battery operating time - backlight on
	Battery operating time - backlight off
	Environmental conditions
	Humity of environment [Min]
	Humity of environment [Max]
	Ambient temperature [Min]
	Ambient temperature [Max]
	Packing & Shipping
	Readability force [d] (N)
	Shipping method
	Dimensions packaging (W×D×H)
	Net weight approx.
	Gross weight approx.

UN number (hazardous goods)

Article number for adjustment at

Services (optional)

the location of installation

Construction	
Dimension housing (W×D×H)	285×255×90 mm
Dimensions weighing surface (W×D)	252×200 mm
Material housing	stainless steel
Material weighing plate	stainless steel
Functions	
Number of keys for operation	4
Auto-off interval(s) in battery mode/rechargeable battery mode	2 min
Tare function	manual (multi)
Underfloor weighing	None
IP protection - complete device	IP67
Power Supplay	
Input voltage power supply / power [Max]	230 V AC, 50 Hz
Input voltage device / power [Max]	15 V, 500 mA
Plug-in power supply type	Power adapter
Supplied plug-in power supply	Battery
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Battery	4×1.5 V AA
Battery operating time	48 h
Battery operating time - backlight on	48 h
Battery operating time - backlight off	66 h
Environmental conditions	
	25.9/
Humity of environment [Min]	25 % 95 %
Humity of environment [Max]	5 °C
Ambient temperature [Min] Ambient temperature [Max]	35 °C
Ambient temperature [iviax]	
Packing & Shipping	
Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	420×305×165 mm

3,8 kg

4,6 kg

3496

961-248

25 mm

KERN FOB 30K-3NL



Stainless steel bench scale with large weighing ranges and IP67 protection against dust and water spray

Article number for DAkkS calibration

963-128

Article number for certificate of conformity (verification)

969-517

Piktogramme

STANDARD













OPTION



