

KERN FOB 3K-3LM

KERN

Compact stainless steel bench scale with EC type approval [M] and special checkweighing display for even more efficient working



Pattern approval for conformity assessment	✓
Accuracy classe	III
Verification scale interval [e]	1 g

Display	
Display digit height	25 mm
Display backlight	✓

Construction	
Dimension housing (W×D×H)	256×285×100 mm
Dimensions weighing surface (W×D)	248×198 mm
Material housing	stainless steel
Material weighing plate	stainless steel

Functions	
Auto-off interval(s) in battery mode/rechargeable battery mode	2 min
Tare function	manual (multi)
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
IP protection - complete device	IP65

Power Supply	
Input voltage power supply / power [Max]	230 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied plug-in power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	EURO UK CH
Battery	4×1.5 V AA
Battery operating time	48 h
Battery operating time - backlight on	48 h
Battery operating time - backlight off	66 h

Environmental conditions	
Humidity of environment [Min]	25 %
Humidity of environment [Max]	95 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C

Category	
Brand	KERN
Product category	Industrial scales
Product group	Food (kitchen/stainless steel/IP65...68 protection)

Measuring System	
Readability [d]	1 g
Weighing capacity [Max]	3000 g
Number of weighing ranges	1
Eccentric loading at 1/3 [Max]	3 g
Minimum weight [Min]	20 g
Reproducibility	1 g
Linearity	± 2 g
Weighing system	Strain gauge
Resolution	3.000
Units	g
Units (if device is conformity assessed)	g
Default unit	g
Stabilization time	2 s
Warm-up time	10 min
Adjustment options	Adjusting with external weight
Recommended adjusting weight	2 kg (M1)
Possible calibration points	3 kg

Approval	
CE mark	✓
Conformity assessment possible ex works	✓

KERN FOB 3K-3LM



Compact stainless steel bench scale with EC type approval [M] and special checkweighing display for even more efficient working

Packing & Shipping

Readability force [d] (N)	1 d
Shipping method	Parcel service
Dimensions packaging (W×D×H)	420×305×180 mm
Net weight approx.	3,8 kg
Gross weight approx.	4,8 kg

Services (optional)

Article number for adjustment at the location of installation	961-247
Article number for conformity assessment	965-227
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Piktogramme

STANDARD



OPTION



FACTORY

