according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: **4379**Version: **2.0 en**date of compilation: 2017-02-28

Revision: 2022-04-12

Replaces version of: 2017-02-28

Version: (1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance **2-Methyl-1-butanol** \geq 97,5%, for synthesis

Article number 4379

Registration number (REACH)

It is not required to list the identified uses be-

cause the substance is not subject to registration

according to REACH (< 1 t/a).

Index number in CLP Annex VI 603-006-00-7
EC number 205-289-9
CAS number 137-32-6

Alternative name(s) sec. Butyl Carbinol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

United Kingdom (en) Page 1 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1I	Acute toxicity (inhal.)		Acute Tox. 4	H332
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Pictograms

GHS02, GHS07



Hazard statements

H226 Flammable liquid and vapour

H332 Harmful if inhaled

H335 May cause respiratory irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking

P260 Do not breathe mist/vapours/spray

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

United Kingdom (en) Page 2 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

Symbol(s)



EUH066

Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance 2-Methyl-1-butanol

Molecular formula $C_5H_{12}O$ Molar mass $88,15 \, {}^g/_{mol}$

CAS No 137-32-6 EC No 205-289-9 Index No 603-006-00-7

Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	11 ^{mg} / _l /4h	inhalation: vapour

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

United Kingdom (en) Page 3 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

4.2 Most important symptoms and effects, both acute and delayed

Headache, Irritation, Cough, Dyspnoea, Vertigo, Nausea, Vomiting, Diarrhoea, Breathing difficulties, Impairment of vision, Agitation, Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

United Kingdom (en) Page 4 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Use extractor hood (laboratory).

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels


Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

United Kingdom (en) Page 5 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



article number: 4379



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	73,16 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	292 mg/m³	human, inhalatory	worker (industry)	acute - local effects

Environmental values

Relevant PNECs and other threshold levels				
End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	0,12 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,012 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
PNEC	37 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0,499 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,05 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,029 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





United Kingdom (en) Page 6 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379





Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

0,4 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless - light yellow
Odour disagreeable - stinging

Melting point/freezing point -70 °C

Boiling point or initial boiling point and boiling 127 – 130 °C

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1,2 vol% (LEL) - 10,5 vol% (UEL) Flash point 42,5 °C at 1.013 hPa (c.c.) (ECHA)

Auto-ignition temperature 340 °C at 1.013 hPa (ECHA) (auto-ignition temper-

ature (liquids and gases))

Decomposition temperature not relevant

pH (value) 7

United Kingdom (en) Page 7 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

Kinematic viscosity not determined

Dynamic viscosity 5,505 mPa s at 19,3 °C

Solubility(ies)

Water solubility 30 ^g/_l at 25 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): 1,29 (pH value: ~7, 20 °C) (ECHA)

4.159 hPa at 20 °C Vapour pressure

Density and/or relative density

Density $0.82 \, {\rm g}/{\rm cm}^3$ at 20 °C

Relative vapour density 3,04 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Other safety characteristics:

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Temperature class (EU, acc. to ATEX) Maximum permissible surface temperature on the equipment: 300°C

There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

United Kingdom (en) Page 8 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if inhaled.

Acute toxicity	Acute	tox	icity
----------------	--------------	-----	-------

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	4.170 ^{mg} / _{kg}	rat		
dermal	LD50	2.900 ^{mg} / _{kg}	rabbit		

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

nausea, dizziness

• If in eyes

slightly irritant but not relevant for classification

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

United Kingdom (en) Page 9 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

• If on skin

has degreasing effect on the skin

Other information

Headache, Nausea, Vertigo, Dizziness, Agitation, Inebriation, Impairment of vision, Vomiting

11.2 Endocrine disrupting properties

Not listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: $2,722 \, ^{mg}/_{mg}$ Theoretical Carbon Dioxide: $2,496 \, ^{mg}/_{mg}$

Process of degradability

Process	Degradation rate	Time
oxygen depletion	70 %	5 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

12.4 Mobility in soil

Henry's law constant	1,34 Pa m³/ _{mol} at 25 °C (ECHA)
----------------------	--

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

United Kingdom (en) Page 10 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN	number	or ID	number
14.1	UN	number	or in	numbe

ADRRID	UN 1105
IMDG-Code	UN 1105
ICAO-TI	UN 1105

14.2 UN proper shipping name

ADRRID	PENTANOLS
IMDG-Code	PENTANOLS
ICAO-TI	Pentanols

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADRRID	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazardsnon-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

United Kingdom (en) Page 11 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379



14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name PENTANOLS

Particulars in the transport document UN1105, PENTANOLS, 3, III, (D/E)

Classification code F1
Danger label(s) 3



Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code 3

Danger label(s) 3



Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
Transport category (TC) 3
Hazard identification No 30

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name PENTANOLS

Particulars in the shipper's declaration UN1105, PENTANOLS, 3, III, 42,5°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP) 223
Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L

United Kingdom (en) Page 12 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

EmS F-E, S-D

Stowage category Α

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name **Pentanols**

Particulars in the shipper's declaration UN1105, Pentanols, 3, III

Danger label(s) 3



Special provisions (SP) **A3** Excepted quantities (EQ) E1 Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)

Name of substance	Name acc. to inventory	CAS No	Restriction	No
2-Methyl-1-butanol	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
2-Methyl-1-butanol	flammable / pyrophoric		R40	40

Legend

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

tricks and jokes,

- games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

2. Articles not complying with paragraph 1 shall not be placed on the market.3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

can be used as fuel in decorative oil lamps for supply to the general public, and present an aspiration hazard and are labelled with H304.

- 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation
- (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil

or even sucking the wick of lamps – may lead to life-threatening lung damage";

(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';

(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black

opaque containers not exceeding 1 litre by 1 December 2010.';

United Kingdom (en) Page 13 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

Legend

R40 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended

for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,

- artificial snow and frost,
- 'whoopee' cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
 decorative flakes and foams,
- artificial cobwebs,
- stink bombs.
- 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.
- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
- 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

2012/18/EU (Seveso III)				
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)

Notation

Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 % 820 ^g / _I
-------------	--

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	820 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

United Kingdom (en) Page 14 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AICS CSCL-ENCS DSL ECSI

IECSC

Australian Inventory of Chemical Substances
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Korea Existing Chemicals Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH registered substances
Taiwan Chemical Substance Inventory
Toxic Substance Control Act

NZIoC

PICCS REACH Reg. TCSI

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

United Kingdom (en) Page 15 / 17

according to Regulation (EC) No. 1907/2006 (REACH)

2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379



SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)	
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)	
ATE	Acute Toxicity Estimate	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	

United Kingdom (en) Page 16 / 17

according to Regulation (EC) No. 1907/2006 (REACH)



2-Methyl-1-butanol ≥ 97,5%, for synthesis

article number: 4379

Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
SVHC	Substance of Very High Concern
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 17 / 17