

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: **4431**  
Version: **5.0 en**  
Replaces version of: 2022-05-18  
Version: (4)

date of compilation: 2015-12-03  
Revision: 2022-12-15

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance	<b>1-Butanol</b> ROTISOLV® ≥99,8 %, UV/IR-Grade
Article number	4431
EC number	200-751-6
CAS number	71-36-3
Alternative name(s)	n-Butanol

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** sicherheit@carlroth.de  
**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** **sicherheit@carlroth.de**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS05,  
GHS07



#### Hazard statements

H226 Flammable liquid and vapour  
H302 Harmful if swallowed  
H315 Causes skin irritation  
H318 Causes serious eye damage  
H335 May cause respiratory irritation  
H336 May cause drowsiness or dizziness

#### Precautionary statements

##### Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P260 Do not breathe mist/vapours  
P280 Wear protective gloves/eye protection

##### Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance	1-Butanol
Molecular formula	C <sub>4</sub> H <sub>10</sub> O
Molar mass	74,12 g/mol
CAS No	71-36-3
EC No	200-751-6

Substance, Specific Conc. Limits, M-factors, ATE			
Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	500 mg/kg	oral

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off contaminated clothing.

#### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Call a doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Cough, Dyspnoea, Irritant effects, Vertigo, Headache, Drowsiness, Dizziness, Narcosis,

Following skin contact: Irritation,

After eye contact: Irritation, Risk of serious damage to eyes, Risk of blindness,

Following ingestion: Vomiting, Nausea

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
GB	butan-1-ol	71-36-3	WEL			50	154				EH40/2005

#### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### Notation

STEL	Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	310 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects

### Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0,082 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,008 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	2.476 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0,324 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,032 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,017 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### • type of material

Butyl caoutchouc (butyl rubber)

### • material thickness

0,5 mm

### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - alcohol
Odour threshold	0,004 – 48,7 ppm
Melting point/freezing point	<-90 °C (ECHA)
Boiling point or initial boiling point and boiling range	119 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1,4 vol% (LEL) - 11,3 vol% (UEL)
Flash point	35 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	355 °C at 1.019 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	7 (in aqueous solution: 70 g/l, 20 °C)
Kinematic viscosity	3,638 mm <sup>2</sup> /s at 20 °C
Dynamic viscosity	2,947 mPa s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	66 g/l at 20 °C (ECHA)

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### Partition coefficient

Partition coefficient n-octanol/water (log value): 1 (pH value: 7, 25 °C) (ECHA)

Soil organic carbon/water (log KOC) 0,54 (ECHA)

Vapour pressure <10 hPa at 20 °C

### Density and/or relative density

Density 0,81 g/cm<sup>3</sup> at 20 °C (ECHA)

Relative vapour density 2,6 at 20 °C (air = 1)

Particle characteristics not relevant (liquid)

### Other safety parameters

Oxidising properties none

## 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Gas group (explosion group) IIB  
Maximum Experimental Safe Gap value; 0,5 mm ≤  
MESG ≤ 0,9 mm

Maximum explosion pressure 8,4 bar

Surface tension 69,9 mN/m (20 °C) (ECHA)

Refractive index 1,399 (20 °C)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition.

#### **If heated**

Risk of ignition. Vapours may form explosive mixtures with air.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Exothermic reaction with:** Alkali metals, Aluminium, Alkaline earth metal, Reducing agents, Acid chlorides, inorganic, Strong oxidisers

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### 10.5 Incompatible materials

aluminium, Rubber articles, different plastics

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Classification acc. to GHS

#### Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	2.292 mg/kg	rat		ECHA
dermal	LD50	3.430 mg/kg	rabbit		ECHA

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

##### • If swallowed

vomiting, nausea

##### • If in eyes

Causes serious eye damage, risk of blindness

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### • If inhaled

Irritation to respiratory tract, cough, Dyspnoea, headache, vertigo, fatigue, dizziness, narcosis

### • If on skin

causes skin irritation

### • Other information

Other adverse effects: Liver and kidney damage, Cardiovascular system

## 11.2 Endocrine disrupting properties

Not listed.

## 11.3 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

#### Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	1.376 mg/l	fish	ECHA	96 h
EC50	1.328 mg/l	aquatic invertebrates	ECHA	48 h
ErC50	225 mg/l	algae	ECHA	96 h

#### Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	18 mg/l	aquatic invertebrates	ECHA	21 d

### 12.2 Persistence and degradability

#### Biodegradation

The substance is readily biodegradable.

#### Process of degradability

Process	Degradation rate	Time
biotic/abiotic	98 %	28 d
oxygen depletion	68 %	5 d

### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	1 (pH value: 7, 25 °C) (ECHA)
---------------------------	-------------------------------

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### 12.4 Mobility in soil

Henry's law constant	0,054 Pa m <sup>3</sup> /mol (ECHA)
The Organic Carbon normalised adsorption coefficient	0,54 (ECHA)

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Not listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Properties of waste which render it hazardous

**HP 3** flammable

**HP 4** irritant - skin irritation and eye damage

**HP 5** specific target organ toxicity (STOT)/aspiration toxicity

**HP 6** acute toxicity

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADRRID UN 1120

IMDG-Code UN 1120

ICAO-TI UN 1120

### 14.2 UN proper shipping name

ADRRID BUTANOLS



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

IMDG-Code	BUTANOLS
ICAO-TI	Butanols
<b>14.3 Transport hazard class(es)</b>	
ADRRID	3
IMDG-Code	3
ICAO-TI	3
<b>14.4 Packing group</b>	
ADRRID	III
IMDG-Code	III
ICAO-TI	III
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	
Provisions for dangerous goods (ADR) should be complied within the premises.	
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
The cargo is not intended to be carried in bulk.	
<b>14.8 Information for each of the UN Model Regulations</b>	
<b>Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information</b>	
Proper shipping name	BUTANOLS
Particulars in the transport document	UN1120, BUTANOLS, 3, III, (D/E)
Classification code	F1
Danger label(s)	3
	
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30
<b>Emergency Action Code</b>	2Y
<b>Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information</b>	
<b>Classification code</b>	F1
<b>Danger label(s)</b>	3
	



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

<b>Excepted quantities (EQ)</b>	E1
<b>Limited quantities (LQ)</b>	5 L
<b>Transport category (TC)</b>	3
<b>Hazard identification No</b>	30
<b>International Maritime Dangerous Goods Code (IMDG) - Additional information</b>	
Proper shipping name	BUTANOLS
Particulars in the shipper's declaration	UN1120, BUTANOLS, 3, III, 35°C c.c.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	223
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	A
<b>International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information</b>	
Proper shipping name	Butanols
Particulars in the shipper's declaration	UN1120, Butanols, 3, III
Danger label(s)	3
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5c	flammable liquids (cat. 2, 3)	5.000      50.000	51)

##### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### Deco-Paint Directive

VOC content	100 % 810 g/l
-------------	------------------

### Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	810 g/l

### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

### Water Framework Directive (WFD)

not listed

### Regulation on the marketing and use of explosives precursors

not listed

### Regulation on drug precursors

not listed

### Regulation on substances that deplete the ozone layer (ODS)

not listed

### Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

### Regulation on persistent organic pollutants (POP)

not listed

### National regulations(GB)

### List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

### Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
1-Butanol	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
1-Butanol	flammable / pyrophoric		40

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed as "ACTIVE"

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1		National inventories: change in the listing (table)	yes

# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)



# Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



## 1-Butanol ROTISOLV® ≥99,8 %, UV/IR-Grade

article number: 4431

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.