

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125	Chromab. columns Kombi-Kit PCB	Page: 1/11
Printing date: 13.01.2023	Date of issue: 26.09.2022	Version: 2.2.2.16

SECTION 1: Identification of the substance/mixture and of the company

1.1 Product identifier

REF 730125
 Product name Chromab. columns Kombi-Kit PCB

REACH Registration number(s): see SECTION 3.1/3.2 or
 A registration number for the substance(s) does not exist because the annual tonnage does not require registration or the substance or its use is excluded from registration.
 25 x 500/500 mg Chromabond® SiOH-H₂ SO₄/SA, PPUFI: HSSV-A3WN-A20T-JS3M
 25 x 500 mg Chromabond® SiOH/PP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses
 Product for analytical use.
 Exposure Scenario Classification according REACH, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0
 The exposure scenario is integrated into sections 1-16.
Uses advised against
 not described

1.3 Details of the supplier of the safety data sheet

Manufactured by:
 MACHEREY-NAGEL GmbH & Co. KG
 Valencienner Str. 11, 52355 Düren, Germany
 Phone: +49 2421 969 0

E-mail: sds@mn-net.com (msds@mn-net.com)

1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service.
 DE: Gemeinsames Giftinformationszentrum (GGIZ)
 99089 Erfurt tel. +49 361 730 730, <<https://www.ggiz-erfurt.de>>

You find our current versions of SDS in Internet:

<<http://www.mn-net.com/SDS>>

Lieferant / Supplier
 Carl Roth GmbH + Co KG
 Schoemperlenstr. 3-5
 76185 Karlsruhe, Germany
 +49 721 5606 0
sicherheit@carlroth.de

SECTION 2: Hazard identification

2.0 Classification of the complete product according to Regulation (EC) 1272/2008



GHS05

Signal word DANGER

Hazard identification	Hazard classes/categories
H314	Skin Corr. 1B

2.1 Classification of the substance or mixture according to Regulation (EC) 1272/2008

500 mg Chromabond® SiOH/PP

Signal word Do not need labelling as hazardous
 -

No hazard class

500/500 mg Chromabond® SiOH-H₂ SO₄/SA, PP



MACHEREY-NAGEL GmbH & Co. KG
 Valencienner Str. 11
 52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
 CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
 FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
 US Tel.: +1 888 321 62 24 sales-us@mn-net.com

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125

Chromab. columns Kombi-Kit PCB

Page: 2/11

Printing date: 13.01.2023

Date of issue: 26.09.2022

Version: 2.2.2.16



GHS05

Signal word

DANGER

Hazard identification

Hazard classes/categories

H314

Skin Corr. 1B

List of H phrases: see section 16.2

2.2 Label elements according regulation (EC) 1272/2008

500 mg Chromabond® SiOH/PP

Do not need labelling as hazardous

Signal word: -

500/500 mg Chromabond® SiOH-H₂SO₄/SA, PP



GHS05

Signal word: DANGER

H314

Causes severe skin burns and eye damage.

P260sh, P280sh, P303+361+353, P305+351+338, P310

Do not breathe dust/vapours. Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Label elements of the complete product



GHS05

Signal word: DANGER

H314

Causes severe skin burns and eye damage.

P260sh, P280sh, P303+361+353, P305+351+338, P310

Do not breathe dust/vapours. Wear protective gloves/eye protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Possible hazards from physicochemical properties

Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive.

Information pertaining to particular risks to human and possible symptoms

Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs.

Information pertaining to particular risks to the environment

Avoid contact of substance/mixture to environment.

PBT: not applicable

vPvB: not applicable



MACHEREY-NAGEL GmbH & Co. KG
Valenciener Str. 11
52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
US Tel.: +1 888 321 62 24 sales-us@mn-net.com

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125

Chromab. columns Kombi-Kit PCB

Page: 3/11

Printing date: 13.01.2023

Date of issue: 26.09.2022

Version: 2.2.2.16

Possible endocrine disrupting effects

no data available

Other hazards

It is not possible to declare fine dust (< 12 µm) as dangerous or not. We recommend not to inhale product dust. Dust may cause damage of the inhalatory system if inhaled over a longer period.

SECTION 3: Composition / information on ingredients

3.1 Substances or 3.2 Mixtures

500/500 mg Chromabond® SiOH-H₂SO₄/SA, PP

Substance name: *sulfuric acid*

CAS No.: 7664-93-9

Substance rating: H314, Skin Corr. 1B

Formula: H₂SO₄ (+H₂O)

REACH Reg. No.: 01-2119458838-20-xxxx

EC No.: 231-639-5

Indice No.: 016-020-00-8

Specific concentration limit: Eye Irrit. 2; H319: 5 % ≤ C < 15 % - Skin Irrit. 2; H315: 5 % ≤ C < 15 % - Skin Corr 1A; H314 c ≥ 15%

Concentration: 30 - <51 %

acc. CLP (GHS): H314, Skin Corr. 1B

Substance name: *silica*

CAS No.: 7631-86-9

Substance rating: No criteria for classification or naming of chemical not required.

Formula: SiO₂

Pseudonym (de): Silicagel, Siliziumdioxid

REACH Reg. No.: 01-2119379499-16-0166

EC No.: 231-545-4

Concentration: 65 - <80 %

acc. CLP (GHS): The criteria for classification are not fulfilled.

500 mg Chromabond® SiOH/PP

Substance name: *silica*

CAS No.: 7631-86-9

Substance rating: No criteria for classification or naming of chemical not required.

Formula: SiO₂

Pseudonym (de): Silicagel, Siliziumdioxid

REACH Reg. No.: 01-2119379499-16-0166

EC No.: 231-545-4

Concentration: 95 - <100 %

acc. CLP (GHS): The criteria for classification are not fulfilled.

3.3 Remarks

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%. List of H and P phrases: see section 16.2.

SECTION 4: First aid measures

4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor.

4.1.1 After SKIN Contact

Remove dust with wetted tissue. Remove contaminated clothing immediately. Rinse the affected skin or mucous membrane thoroughly for min. 15 minutes under running water. Avoid neutralisation. Then apply a loose bandage.

4.1.2 After EYE Contact



MACHEREY-NAGEL GmbH & Co. KG
Valencienner Str. 11
52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
US Tel.: +1 888 321 62 24 sales-us@mn-net.com

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125

Chromab. columns Kombi-Kit PCB

Page: 4/11

Printing date: 13.01.2023

Date of issue: 26.09.2022

Version: 2.2.2.16

Rub dust with teardrops from eyes or: After contact with the eyes rinse thoroughly under running water with the eyelid wide open for min. 10 minutes with eye washing bottle, eye douche or running water (protect intact eye). Before (if possible) apply eye drops Proxymetacaine 0.5%, if the opening the eyelid convulsion is painful. Further treatment to be carried out by an eye specialist.

4.1.3 After INHALATION of vapours

If vomiting and if insensible place patient in recovery position and keep airways free. After inhalation of dust fresh air should be inhaled. ---

4.1.4 After ORAL Intake

After oral intake lots of water with activated charcoal supplement should be drunk after it has been ingested. Do not induce vomiting under any circumstances. Do not make any efforts to neutralise it. Contact medical advice for possible consequences.

4.2 Most important symptoms and effects, both acute and delayed

Rapid penetration and destruction of the skin. Especially in the heated form.
Causes severe skin burns and eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

CORROSIVE DAMAGE: After SKIN CONTACT rinse with water for a long time. Efforts to neutralise the substance can frequently make matters worse. Apply glucocorticosteroides following inflammatory reactions. After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must to be carried out by an eye specialist. After INTAKE administer aluminium oxide drug suspensions. Administer a prophylaxis to counter pulmonary oedema following the INGESTION of corrosive aerosols. In the event of RESPIRATORY DISTRESSES ensure that the patient inhales oxygen. ---

SECTION 5: Firefighting measures

5.1 Extinguishing media

5.1.1 Suitable extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

5.1.2 Unsuitable extinguishing media

no data available

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

Product package burns like paper or plastic.

For great amount - if necessary - protective breathing apparatus which is independent of the ambient air (isolated equipment), and sealed protective clothing is necessary in the event of a large-scale formation of toxic substances.

5.4 Additional information

Danger for environment **only in the event of a large-scale leakage** or formation of hazardous substances.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dusting. Do not breathe dust. Wear suitable protective gloves (see 8.2.2). Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.

6.2 Environmental precautions

Avoid contact of substance/mixture to environment.

PBT: not applicable

vPvB: not applicable

6.3 Methods and material for containment and cleaning up

Remove remaining dust with a vacuum cleaner. If there is no vacuum cleaner, wet dust well and remove mechanical (Inhalation protection). And dispose in accordance to local regulations for the disposal of hazardous chemicals. Clean any contaminated equipment and floors with plenty of water.

6.4 Reference to other sections

see information in section 5.4,7,8 and 13



MACHEREY-NAGEL GmbH & Co. KG
Valencienner Str. 11
52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
US Tel.: +1 888 321 62 24 sales-us@mn-net.com

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125

Chromab. columns Kombi-Kit PCB

Page: 5/11

Printing date: 13.01.2023

Date of issue: 26.09.2022

Version: 2.2.2.16

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid dusting.

7.2 Conditions for safe storage, including any incompatibilities

Safe storage is guaranteed in the original packaging. Storage class (German chemical industry): see chapter 12.1

Storage class (VCI): 8B

Water hazard class (DE): 1

7.2.1 Requirements for stock rooms and containers

Keep original product packages tightly closed during handling and storage. Use unbreakable container for transport of glass bottles.

7.3 Specific end use(s)

Product for analytical use.

SECTION 8: Exposure controls /personal protection

8.1 Control parameters

500/500 mg Chromabond® SiOH-H₂SO₄/SA, PP

Chemical: *sulfuric acid*

CAS No.: 7664-93-9

DNEL: [inh] 50 µg/m³
DNEL = Derived No-Effect Level (for workers)

PNEC (fresh water): 2.5 µg/L
PNEC = Predicted No Effect Concentration

EU value: 0.1 e mg/m³

TRGS 900 (DE): 0.1 E mg/m³
E/e respirable

Short-term exposure factor: 1 (I), Y
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 0,1 e mg/m³

NIOSH: NTP Report on Carcinogens (RoC) List Yes (Known to be a human carcinogen); [TWA] 1 mg/m³
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 1 mg/m³

Chemical: *silica*

CAS No.: 7631-86-9

DNEL: [inh] 4 mg/m³
DNEL = Derived No-Effect Level (for workers)

PNEC (fresh water): -
PNEC = Predicted No Effect Concentration

TRGS 900 (DE): 1,25 A / 4 E mg/m³
E/e respirable

Short-term exposure factor: Y
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 4 e mg/m³

NIOSH: Occupational Carcinogen List yes; [TWA] 6 mg/m³
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 20 mppcf / 80 mg/m³

500 mg Chromabond® SiOH/PP

Chemical: *silica*

CAS No.: 7631-86-9

DNEL: [inh] 4 mg/m³
DNEL = Derived No-Effect Level (for workers)

PNEC (fresh water): -
PNEC = Predicted No Effect Concentration

TRGS 900 (DE): 1,25 A / 4 E mg/m³
E/e respirable

Short-term exposure factor: Y
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 4 e mg/m³

NIOSH: Occupational Carcinogen List yes; [TWA] 6 mg/m³
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 20 mppcf / 80 mg/m³



Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125	Chromab. columns Kombi-Kit PCB	Page: 6/11
Printing date: 13.01.2023	Date of issue: 26.09.2022	Version: 2.2.2.16

8.2 Exposure controls

The highest level of cleanliness must be maintained at the workplace.

- 8.2.1 Respiratory protection**
Use for regularly working with dry powders a dust mask or a dust protection filter, class P3. No additional recommendations.
- 8.2.2 Skin protection / Hand protection**
Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.
- 8.2.3 Eye / Face Protection**
Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.
- 8.2.4 Skin protection**
Recommended to avoid clothing damage, and to avoid contamination with these hazards.
- 8.2.5 Personal hygiene**
Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.
- 8.2.6 Thermal hazards**
no data available

8.3 Limitation and monitoring of environmental exposure

Do not release product into environment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

500/500 mg Chromabond® SiOH-H₂SO₄/SA, PP

a) State of aggregation:	solid
b) Colour:	colourless
c) Odor:	odorless
d) Melting point:	no data available
e) Boiling point:	no data available
f) Flammability:	no data available
g) Explosive limits (lower / upper):	no data available
h) Flash point:	no data available
i) Flashing temperature:	no data available
j) Decomposition temperature:	no data available
k) pH value:	0-1
l) Kinematic viscosity:	no data available
m) Solubility in water:	no data available
n) Dispersion coefficient (o/w) :	no data available
o) Vapour pressure (20°C):	no data available
p) Specific gravity:	no data available
q) Relative vapour density (air=1) :	no data available
r) Particle size:	no data available

500 mg Chromabond® SiOH/PP

a) State of aggregation:	powder (solid)
b) Colour:	colourless
c) Odor:	odorless
d) Melting point:	no data available
e) Boiling point:	no data available
f) Flammability:	no data available
g) Explosive limits (lower / upper):	no data available
h) Flash point:	no data available
i) Flashing temperature:	no data available
j) Decomposition temperature:	no data available
k) pH value:	no data available
l) Kinematic viscosity:	no data available
m) Solubility in water:	0 %
n) Dispersion coefficient (o/w) :	no data available
o) Vapour pressure (20°C):	no data available
p) Specific gravity:	no data available
q) Relative vapour density (air=1) :	no data available
r) Particle size:	45 µm



Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125

Chromab. columns Kombi-Kit PCB

Page: 7/11

Printing date: 13.01.2023

Date of issue: 26.09.2022

Version: 2.2.2.16

9.2 Other information

Properties relevant to substance groups

Substances are highly corrosive.

SECTION 10: Stability and reactivity

10.1 Reactivity

Strong CORROSIVE, no further data available.

10.2 Chemical stability

no known instability.

10.3 Possibility of hazardous reactions

Can react violently with organic material. No further data available.

10.4 Conditions to avoid

No more required.

10.5 Incompatible materials

no additional data available

10.6 Hazardous decomposition products

In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions.

SECTION 11: Toxicological information

11.1 Information on the hazard classes according regulation (EC) 1272/2008

Following information is valid for pure substances. Quantitative data on the toxicity of this product are not available.

500/500 mg Chromabond® SiOH-H₂SO₄/SA, PP

Chemical: *sulfuric acid* CAS No.: 7664-93-9
 TSCA Inventory: listed California Proposition 65 List: not listed
 ACGIH: 1 ppm
 Exposure Routes: inhalation, ingestion, skin and/or eye contact
 Target Organs: Eyes, skin, respiratory system, teeth
 Symptoms: irritation eyes, skin, nose, throat; pulmonary edema, bronchitis; emphysema; conjunctivitis; stomatis; dental erosion; eye, skin burns; dermatitis
 Australia NICNAS: not listed Canada CEPA 1999: DSL Yes
 Japan CSCL/PRTR: not listed, Japan PDSCL: Deleterious Substance
 Japan ISHL: listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)
 South Korea TCCA: Accident Precaution Chemical Yes
 Korea Exist.Chem.Inventory: KE-32570, >10% Toxic 97-1-405, Acc. Precaution Chem.
 LD50 orl rat : 2140 mg/kg
 LC50 ihl mus : 0,85 mg/L/4H

TRGS 905 (DE): Kat 4

Chemical: *silica* CAS No.: 7631-86-9
 TSCA Inventory: listed California Proposition 65 List: not listed
 Exposure Routes: inhalation, skin and/or eye contact
 Target Organs: Eyes, respiratory system
 Symptoms: irritation eyes, pneumoconiosis
 Australia NICNAS: not listed Canada CEPA 1999: DSL yes
 Japan CSCL/PRTR: not listed, Japan PDSCL: not listed
 Japan ISHL: listed ≥0,1%/≥0,1%, Article 57-2 (SDS required)
 South Korea TCCA: not listed
 Korea Exist.Chem.Inventory: KE-31032
 LD50 orl rat : 5000 mg/kg
 LC50 ihl rat : 2,19-5,01 mg/L/4H

TRGS 905 (DE): R F C



Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125	Chromab. columns Kombi-Kit PCB	Page: 8/11
Printing date: 13.01.2023	Date of issue: 26.09.2022	Version: 2.2.2.16

500 mg Chromabond® SiOH/PP
 Chemical: *silica* CAS No.: 7631-86-9
 TSCA Inventory: listed California Proposition 65 List: not listed
 Exposure Routes: inhalation, skin and/or eye contact
 Target Organs: Eyes, respiratory system
 Symptoms: irritation eyes, pneumoconiosis
 Australia NICNAS: not listed Canada CEPA 1999: DSL yes
 Japan CSCL/PRTR: not listed, Japan PDSCL: not listed
 Japan ISHL: listed ≥0,1%/≥0,1%, Article 57-2 (SDS required)
 South Korea TCCA: not listed
 Korea Exist.Chem.Inventory: KE-31032
 LD50 orl rat : 5000 mg/kg
 LC50 ihl rat : 2,19-5,01 mg/L/4H
 TRGS 905 (DE): R F C

11.2 Other hazards

Possible endocrine disrupting effects
 no data available

Other information
 no additional data available

SECTION 12: Ecological information

12.1 Toxicity

Following information is valid for pure substances.

500/500 mg Chromabond® SiOH-H₂SO₄/SA, PP
 Chemical: *sulfuric acid* CAS No.: 7664-93-9
 PNEC (fresh water) : 2.5 µg/L
 PNEC = Predicted No Effect Concentration
 LC50 fish/96h : [NOEC, 65d] 25 µg/L
 EC50 daphnia/48h : 100 mg/L
 EC10 pseudomonas putida/16h : [72h] 100 mg/L
 Water hazard class (DE): 1 WGK No.: 0182
 Storage class (VCI): 8 B

Chemical: *silica* CAS No.: 7631-86-9
 PNEC (fresh water) : -
 PNEC = Predicted No Effect Concentration
 LC50 fish/96h : [4d] 1033-1289 mg/L
 EC50 daphnia/48h : 512; [4d] 2600 mg/L
 EC50 chlorella vulgaris/5d : [4d] 218 mg/L
 Water hazard class (DE): nwg WGK No.: 0849
 Storage class (VCI): 13

500 mg Chromabond® SiOH/PP
 Chemical: *silica* CAS No.: 7631-86-9
 PNEC (fresh water) : -
 PNEC = Predicted No Effect Concentration
 LC50 fish/96h : [4d] 1033-1289 mg/L
 EC50 daphnia/48h : 512; [4d] 2600 mg/L
 EC50 chlorella vulgaris/5d : [4d] 218 mg/L
 Water hazard class (DE): nwg WGK No.: 0849
 Storage class (VCI): 13

12.2 Persistence and degradability

not necessary

12.3 Bioaccumulative potential

not necessary

12.4 Mobility in soil



Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125

Chromab. columns Kombi-Kit PCB

Page: 9/11

Printing date: 13.01.2023

Date of issue: 26.09.2022

Version: 2.2.2.16

not necessary

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher

12.6 Endocrine disrupting properties

no data available

12.7 Other adverse effects

no additional data available

SECTION 13: Disposal considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

13.1 Waste treatment methods

SECTION 14: Transport information

De Minimis (excepted quantities: $\leq 1 \text{ g}/\Sigma \leq 100 \text{ g}$) = ADR 3.5.1.4 = IATA-DRG 2.6.10

14.5 Environmental hazards

none

14.6 Special precautions for user

not necessary

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Dangerous Substances Protection Act (DE: Chemikaliengesetz - ChemG), Aug 2013, Stand: Okt 2020
 Ordinance on protection against dangerous substances (E: Gefahrstoffverordnung - GefStoffV), Nov 2010, Stand: Mrz 2017
 TRGS 201, Classification and labeling of activities involving hazardous substances, Feb 2017
 TRGS 220, National aspects when preparing safety data sheets, Jan 2017
 TRGS 400, Risk assessment for activities involving hazardous substances, Jul 2017
 TRGS 401, Skin contact hazard - identification, assessment, action, Jun 2008, status: Feb 2011
 BekGS 408, Application of the GefStoffV and the TRGS with the entry into force of the CLP regulation, December 2009, status: Jan 2012
 TRGS 500, Protective measures, Mai 2008
 TRGS 510, Storage of hazardous substances in portable containers from March 2013, status: Oct 2015
 Wasserhaushaltsgesetz - WHG, Section 3 Handling substances hazardous to water, Jul 2009, status: Aug 2016
 If necessary, observe other country-specific regulations.

15.2 Chemical safety assessment

not necessary for these small amounts

SECTION 16: Other information

16.1 Changes compared to the last version

Between versions 2.2.2.16 and 2.2.2.2 following changes were applied: - 14 substance data corrected

16.2 List of H and P phrases

16.2.1 List of relevant H phrases

H314 Causes severe skin burns and eye damage.

16.2.2 List of relevant P phrases

P260sh Do not breathe dust/vapours.



MACHEREY-NAGEL GmbH & Co. KG
 Valencienner Str. 11
 52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
 CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
 FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
 US Tel.: +1 888 321 62 24 sales-us@mn-net.com

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125	Chromab. columns Kombi-Kit PCB	Page: 10/11
Printing date: 13.01.2023	Date of issue: 26.09.2022	Version: 2.2.2.16

P280sh	Wear protective gloves/eye protection.
P303+361+353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

16.3 Recommended restriction on use

Only for professional user.
 Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)!
 Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EEC or for DE §§ 11-13 MuSchG 2017)!
 An individual package of this product or test kit has a moderate hazardous potential.

16.4 Sources of key data

KÜHN, BIRETT, Leaflets on hazardous materials, 2021
 Directive 97/69/EG, mineral fibers Directive 1999/92/EG Minimum requirements to improve the safety and health protection of workers at risk from potentially explosive atmospheres
 TRGS 521, German engineering regulations for rehabilitation, repair and demolition with old mineral wool, February 2008 , TRGS 521 "Mineral fibres" in the new version SUVA .CH, limit values in the air at work 2009, revised on 01/2009
 Regulation 790/2009/EU, adaptation of Regulation 1272/2008/EU to technical and scientific progress (1st ATP)
 Regulation 453/2010/EU, adaptation of the REACH regulation 1907/2006/EG
 TRGS 559, German technical rules for mineral dusts from July 2011 Regulation 487/2013/EU, adaptation of regulation 1272/2008/EG to technical and scientific progress (4th ATP)
 Regulation 1221/2015/EU, adaptation of regulation 1272/2008/EG to technical and scientific progress (7th ATP)
 Regulation 776/2017/EU, adaptation of regulation 1272/2008/EG to technical and scientific progress (10th ATP)

 Regulation 669/2018/EU, adaptation of Regulation 1272/2008/EC to technical and scientific progress Text (11th ATP)
 Regulation 1480/2018/EU, adaptation of regulation 1272/2008/EG to technical and scientific progress (13th ATP)
 Regulation 521/2019/EU, adaptation of regulation 1272/2008/EG to technical and scientific progress (12th ATP)
 TRGS 900, German rules of technology on limit values in the air at work, as of 03/2019
 Regulation 217/2020/EU, adaptation of Annex VI, Part 3, of Regulation 1272/2008/EC to technical and scientific progress (14th ATP)
 Regulation 878/2020/EU, adaptation of Annex II of the REACH regulation 1907/2006/EG
 Regulation 1182/2020/EU, adaptation of Annex VI, Part 3, of Regulation 1272/2008/EC to technical and scientific progress (15th ATP)
 Regulation 643/2021/EU, adaptation of Annex VI, Part 1, of Regulation 1272/2008/EC to technical and scientific progress (16th ATP)
 Regulation 849/2021/EU, adaptation of Annex VI, Part 3, of Regulation 1272/2008/EC to technical and scientific progress (17th ATP)

revisions/updates

Reason for revision: *2014-02 Corrected structure of the sections according to Regulation 453/2010/EU, if necessary*
2014-04 adjustment according Regulation 487/2013/EU
2016-03 adjustment according Regulation 1221/2015/EU

2017-11 adjustment according the ECHA registration dossier
2022-11 adjustment according Regulation 878/2020/EU

16.5 Further information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.
 MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

16.6 Legend / Abbreviations

acc:	according
ADR:	Convention concerning the International Carriage of Dangerous Goods by Road
Act:	acute
BAT:	biological workplace tolerance value
CAO:	Cargo Aircraft Only
Carc:	carcinogen
CAS:	Chemical Abstracts Service
CLP:	Classification, Labelling and Packaging regulation
CMR:	carcinogen, mutagen, reproduction toxic
Corr:	corrosive
COD:	chemical oxygen demand
CSCL:	Chemical Substance Control Law (Jp)
Dam:	damage
DNEL:	Derived No-Effect Level (for workers)
derm:	dermal



MACHEREY-NAGEL GmbH & Co. KG
 Valenciener Str. 11
 52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
 CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
 FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
 US Tel.: +1 888 321 62 24 sales-us@mn-net.com

Safety Data Sheet

according to Regulations 1907/2006/EC (REACH) and 2015/830/EU

REF: 730125	Chromab. columns Kombi-Kit PCB	Page: 11/11
Printing date: 13.01.2023	Date of issue: 26.09.2022	Version: 2.2.2.16

- dog: dog
- EC10: Concentration causing a toxic effect in 10% of the test organisms
- EC: European Community
- EC-Nr: Substance number of the EC substance inventory
- EmS: Guide to accident management measures on ships
- EU: European Union
- fish: fish (not specified)
- GHS: Global Harmonized System of Classification and Labeling of Chemicals
- gpg: guinea pig
- ICAO: International Civil Aviation Organization
- ihl: inhaled
- IMDG: International Maritime Dangerous Goods Code
- intrav: intravenous
- ipt: intraperitoneal
- ISHL: Industrial Safety and Health Law (Jp)
- LC50: letale concentration 50%
- LD50: letale dosis 50%
- leuciscus idus: fisch, ide, orfe
- MAK: maximum workplace concentration
- Met: Metall
- mus: mouse
- Muta: mutagen
- NIOSH: National Institute for Occupational Safety and Health (US)
- NRD: Non-rapidly degradable
- onchorhynchus mykiss: fisch, rainbow trout
- ori: oral
- OSHA: Occupational Safety and Health Administration
- PAX: transport on passenger planes allowed
- PBT: persistent, bioaccumulating, toxic substance
- pH: pH value
- pimephales promelas: fisch, fathead minnow
- PNEC: Predicted No Effect Concentration
- PROC 15: Process category 'for laboratory use'
- PRTR: Law for PRTR and Promotion of Chemical Management (Jp)
- PVC: polyvinyl chloride
- quail: bird, quail
- rat: rat
- rbt: rabbit
- RD: rapidly degradable
- RE: repeated
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- REF: item number, reference number
- Reg.No.: rRegistration number
- Repr: harmful to reproduction
- Resp: respiratory
- RIP: REACH Implementations Projects
- scu: sub cutan
- SDS: safety data sheet
- Sens: sensitisation
- STEL: short term exposure limit
- STOT: Specific Target Organ Toxicity
- SVHC: Substance of Very High Concern
- t/a: tons per year
- TCCA: Toxic Chemicals Control Act (S. Korea)
- Tox: toxic
- TSCA: The Toxic Substances Control Act (US)
- TWA: time weighted average
- TRGS: technical regulations (DE)
- vPvB: very persistent, very bioaccumulating substance

16.7 Training advice

Regular safety training. Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products.



MACHEREY-NAGEL GmbH & Co. KG
 Valenciener Str. 11
 52355 Düren · Germany
www.mn-net.com

DE Tel.: +49 24 21 969-0 info@mn-net.com
 CH Tel.: +41 62 388 55 00 sales-ch@mn-net.com
 FR Tel.: +33 388 68 22 68 sales-fr@mn-net.com
 US Tel.: +1 888 321 62 24 sales-us@mn-net.com